


XY800




Dimensions		
Poles:	2P-12P	
Pitch:	8.0mm(.315")	
Electrical		
Standard:	UL	IEC
Voltage Rating:	300V	450V
Current Rating:	15A	32A
Wire range:	20-12AWG 0.5-4.0mm ²	
Withstand voltage	AC2000V/Min	
Mechanical		
Torque:	0.5N.m(4.4Lb-In.)	
Ambient temperature	-40°C~+105°C	
Material		
Housing:	PA66(UL 94V-0)	
Current carrier:	Brass,Nickel Plated Steel ,Cr3+ Zn plated	
Screw:	M2.5,Steel(A3),Zinc Plated	



XY800H




Dimensions		
Poles:	2P-12P	
Pitch:	8.0mm(.315")	
Electrical		
Standard:	UL	IEC
Voltage Rating:	300V	450V
Current Rating:	15A	32A
Wire range:	20-12AWG 0.5-4.0mm ²	
Withstand voltage	AC2000V/Min	
Mechanical		
Torque:	0.5N.m(4.4Lb-In.)	
Ambient temperature	-40°C~+105°C	
Material		
Housing:	PA66(UL 94V-0)	
Current carrier:	Brass,Nickel Plated Steel ,Cr3+ Zn plated	
Screw:	M2.5,Steel(A3),Zinc Plated	



XY800W




Dimensions		
Poles:	2P-12P	
Pitch:	8.0mm(.315")	
Electrical		
Standard:	UL	IEC
Voltage Rating:	300V	450V
Current Rating:	15A	24A
Wire range:	20-14AWG 0.5-2.5mm ²	
Withstand voltage	AC2000V/Min	
Mechanical		
Torque:	0.5N.m(4.4Lb-In.)	
Ambient temperature	-40°C~+105°C	
Material		
Housing:	PA66(UL 94V-0)	
Current carrier:	Brass,Nickel Plated Steel ,Cr3+ Zn plated	
Screw:	M2.5,Steel(A3),Zinc Plated	
Wire guard	Stainless Steel	



XY800HW




Dimensions		
Poles:	2P-12P	
Pitch:	8.0mm(.315")	
Electrical		
Standard:	UL	IEC
Voltage Rating:	300V	450V
Current Rating:	15A	24A
Wire range:	20-14AWG 0.5-2.5mm ²	
Withstand voltage	AC2000V/Min	
Mechanical		
Torque:	0.5N.m(4.4Lb-In.)	
Ambient temperature	-40°C~+105°C	
Material		
Housing:	PA66(UL 94V-0)	
Current carrier:	Brass,Nickel Plated Steel ,Cr3+ Zn plated	
Screw:	M2.5,Steel(A3),Zinc Plated	
Wire guard	Stainless Steel	



XY801




Dimensions		
Poles:	2P-12P	
Pitch:	10.0mm(.394")	
Electrical		
Standard:	UL	IEC
Voltage Rating:	300V	450V
Current Rating:	20A	41A
Wire range:	18-10AWG 1-6.0mm ²	
Withstand voltage	AC2000V/Min	
Mechanical		
Torque:	0.5N.m(4.4Lb-In.)	
Ambient temperature	-40°C~+105°C	
Material		
Housing:	PA66(UL 94V-0)	
Current carrier:	Brass,Nickel Plated Steel ,Cr3+ Zn plated	
Screw:	M3,Steel(A3),Zinc Plated	



XY801H



Dimensions		
Poles:	2P-12P	
Pitch:	10.0mm(.394")	
Electrical		
Standard:	UL	IEC
Voltage Rating:	300V	450V
Current Rating:	20A	41A
Wire range:	18-10AWG 1-6.0mm ²	
Withstand voltage	AC2000V/Min	
Mechanical		
Torque:	0.5N.m(4.4Lb-In.)	
Ambient temperature	-40°C~+105°C	
Material		
Housing:	PA66(UL 94V-0)	
Current carrier:	Brass,Nickel Plated Steel ,Cr3+ Zn plated	
Screw:	M3,Steel(A3),Zinc Plated	



Feed Through Terminal Block


XY801W



Dimensions	
Poles:	2P-12P
Pitch:	10.0mm(.394")
Electrical	
Standard:	UL IEC
Voltage Rating:	300V 450V
Current Rating:	20A 32A
Wire range:	18-12AWG 0.5-4.0mm ²
Withstand voltage	AC2000V/Min

Mechanical	
Torque:	0.5N.m(4.4Lb-In.)
Ambient temperature	-40°C~+105°C

Material	
Housing:	PA66(UL 94V-0)
Current carrier:	Brass,Nickel Plated Steel ,Cr3+ Zn plated
Screw:	M3,Steel(A3),Zinc Plated
Wire guard	Stainless Steel




XY801HW



Dimensions	
Poles:	2P-12P
Pitch:	10.0mm(.394")
Electrical	
Standard:	UL IEC
Voltage Rating:	300V 450V
Current Rating:	20A 32A
Wire range:	18-12AWG 0.5-4.0mm ²
Withstand voltage	AC2000V/Min

Mechanical	
Torque:	0.5N.m(4.4Lb-In.)
Ambient temperature	-40°C~+105°C

Material	
Housing:	PA66(UL 94V-0)
Current carrier:	Brass,Nickel Plated Steel ,Cr3+ Zn plated
Screw:	M3,Steel(A3),Zinc Plated
Wire guard	Stainless Steel




XY802



Dimensions	
Poles:	2P-12P
Pitch:	12.0mm(.473")
Electrical	
Standard:	UL IEC
Voltage Rating:	300V 750V
Current Rating:	30A 57A
Wire range:	14-10AWG 2.5-10.0mm ²
Withstand voltage	AC2000V/Min

Mechanical	
Torque:	0.6N.m(5.3Lb-In.)
Ambient temperature	-40°C~+105°C

Material	
Housing:	PA66(UL 94V-0)
Current carrier:	Brass,Nickel Plated Steel ,Cr3+ Zn plated
Screw:	M3.5,Steel(A3),Zinc Plated




XY802H



Dimensions	
Poles:	2P-12P
Pitch:	12.0mm(.473")
Electrical	
Standard:	UL IEC
Voltage Rating:	300V 750V
Current Rating:	30A 57A
Wire range:	14-10AWG 2.5-10.0mm ²
Withstand voltage	AC2000V/Min

Mechanical	
Torque:	0.6N.m(5.3Lb-In.)
Ambient temperature	-40°C~+105°C

Material	
Housing:	PA66(UL 94V-0)
Current carrier:	Brass,Nickel Plated Steel ,Cr3+ Zn plated
Screw:	M3.5,Steel(A3),Zinc Plated




XY802W



Dimensions	
Poles:	2P-12P
Pitch:	12.0mm(.473")
Electrical	
Standard:	UL IEC
Voltage Rating:	300V 750V
Current Rating:	30A 41A
Wire range:	14-10AWG 2.5-6.0mm ²
Withstand voltage	AC2000V/Min

Mechanical	
Torque:	0.6N.m(5.3Lb-In.)
Ambient temperature	-40°C~+105°C

Material	
Housing:	PA66(UL 94V-0)
Current carrier:	Brass,Nickel Plated Steel ,Cr3+ Zn plated
Screw:	M3.5,Steel(A3),Zinc Plated
Wire guard	Stainless Steel




XY802HW



Dimensions	
Poles:	2P-12P
Pitch:	12.0mm(.473")
Electrical	
Standard:	UL IEC
Voltage Rating:	300V 750V
Current Rating:	30A 41A
Wire range:	14-10AWG 2.5-6.0mm ²
Withstand voltage	AC2000V/Min

Mechanical	
Torque:	0.6N.m(5.3Lb-In.)
Ambient temperature	-40°C~+105°C


Material	
Housing:	PA66(UL 94V-0)
Current carrier:	Brass,Nickel Plated Steel ,Cr3+ Zn plated
Screw:	M3.5,Steel(A3),Zinc Plated
Wire guard	Stainless Steel



XY803




Dimensions			
Poles:	2P-12P		
Pitch:	13.5mm(.531")		
Electrical			
Standard:	UL	IEC	
Voltage Rating:	300V	750V	
Current Rating:	48A	57A	
Wire range:	12-8AWG		
Mechanical			
Torque:	0.8N.m(7.06Lb-In.)		
Ambient temperature	-40°C~+105°C		
Material			
Housing:	PA66(UL 94V-0)		
Terminal Block:	Brass,Nickel Plated Steel ,Cr3+ Zn plated		
Screw:	M4,Steel(A3),Zinc Plated		



XY803W




Dimensions			
Poles:	2P-12P		
Pitch:	13.5mm		
Electrical			
Standard:	UL	IEC	
Voltage Rating:	300V	750V	
Current Rating:	48A	57A	
Wire range:	12-8AWG		
Mechanical			
Torque:	0.8N.m(7.06Lb-In.)		
Ambient temperature	-40°C~+105°C		
Material			
Housing:	PA66(UL 94V-0)		
Terminal Block:	Brass,Nickel Plated Steel ,Cr3+ Zn plated		
Screw:	M4,Steel(A3),Zinc Plated		
Wire guard	Stainless Steel		



XY804




Dimensions			
Poles:	2P-12P		
Pitch:	14.5mm(.571")		
Electrical			
Standard:	UL	IEC	
Voltage Rating:	300V	750V	
Current Rating:	60A	76A	
Wire range:	14-6AWG		
Mechanical			
Torque:	0.8N.m(7.06Lb-In.)		
Ambient temperature	-40°C~+105°C		
Material			
Housing:	PA66(UL 94V-0)		
Terminal Block:	Brass,Nickel Plated Steel ,Cr3+ Zn plated		
Screw:	M5,Steel(A3),Zinc Plated		



XY804W




Dimensions			
Poles:	2P-12P		
Pitch:	14.5mm(.571")		
Electrical			
Standard:	UL	IEC	
Voltage Rating:	300V	750V	
Current Rating:	60A	76A	
Wire range:	8-6AWG		
Mechanical			
Torque:	0.8N.m(7.06Lb-In.)		
Ambient temperature	-40°C~+105°C		
Material			
Housing:	PA66(UL 94V-0)		
Terminal Block:	Brass,Nickel Plated Steel ,Cr3+ Zn plated		
Screw:	M5,Steel(A3),Zinc Plated		
Wire guard	Stainless Steel		



XY806A




Dimensions			
Poles:	1P-5P		
Pitch:	10mm(.394")		
Electrical			
Standard:	UL	IEC	
Voltage Rating:	300V	450V	
Current Rating:	10A	7.5A	
Wire range:	18-14AWG		
Mechanical			
Torque:	0.5N.m(4.5Lb-In.)		
Ambient temperature	-40°C~+105°C		
Strip length	6-7mm		
Material			
Housing:	PA66(UL 94V-0)		
Terminal Block:	Brass,Nickel Plated		
Screw:	M3,Steel(A3),Zinc Plated		



XY806B



Dimensions			
Poles:	1P-5P		
Pitch:	10.0mm(.394")		
Electrical			
Standard:	UL	IEC	
Voltage Rating:	300V	450V	
Current Rating:	10A	7.5A	
Wire range:	22-14AWG	0.5-2.5mm ²	
Withstand voltage	AC2000V/Min		
Mechanical			
Torque:	0.5N.m(4.5Lb-In.)		
Ambient temperature	-40°C~+105°C		
Strip length	6-7mm		
Material			
Housing:	PA66(UL 94V-0)		
Terminal Block:	Brass,Nickel Plated		
Screw:	M3,Steel(A3),Zinc Plated		



Feed Through Terminal Block

XY806C




Dimensions
 Poles: 1P-5P(.394")
 Pitch: 10mm

Electrical
 Standard: UL IEC
 Voltage Rating: 300V 450V
 Current Rating: 10A 7.5A
 Wire range: 18-14AWG

Mechanical
 Torque: 0.5N.m(4.5Lb-In.)
 Ambient temperature: -40°C~+105°C
 Strip length: 6-7mm

Material
 Housing: PA66(UL 94V-0)
 Terminal Block: Brass,Nickel Plated
 Screw: M3,Steel(A3),Zinc Plated



XY126 TO DC2.1 mm F




Dimensions
 Poles: 2P,3P-24P
 Pitch: 5.0mm(.197")

Electrical
 Standard: UL IEC
 Voltage Rating: 300V 250V
 Current Rating: 10A 10A
 Wire range: 26-14AWG 0.5-2.5mm²
 Withstand voltage: AC2000V/Min

Mechanical
 Torque: 0.4N.m(3.5Lb-In.)
 Ambient temperature: -40°C~+105°C
 Strip length: 6-7mm

Material
 Housing: PA66(UL 94V-0)
 Wire guard: Stainless Steel
 Pin header: Brass,Tin Plated
 Screw: M2.5,steel,A3 Zn plated



XY126 TO DC2.1 mm M



Dimensions
 Poles: 2P,3P-24P
 Pitch: 5.0mm(.197")

Electrical
 Standard: UL IEC
 Voltage Rating: 300V 250V
 Current Rating: 10A 10A
 Wire range: 26-14AWG 0.5-2.5mm²
 Withstand voltage: AC2000V/Min

Mechanical
 Torque: 0.4N.m(3.5Lb-In.)
 Ambient temperature: -40°C~+105°C
 Strip length: 6-7mm

Material
 Housing: PA66(UL 94V-0)
 Wire guard: Stainless Steel
 Pin header: Brass,Tin Plated
 Screw: M2.5,steel,A3 Zn plated

